



Clear zipper bag 5 gallon Oil only spill kit

SK-OZB

Spill kit | 5 Gallon | Oil only | Clear zipper bag

Absorbency: 8 US Gallons | 30 Liters**

Base Fiber: polypropylene



Product Code	Color	Format	Size inches(cm)	Recycled Content	Units/Case	LTL/Pallet	FTL/Pallet
SK-OZB	White	Spill kit	15" x 18" x 3" (38 x 46 x 8)	-	4	20	20

Zip-top clear plastic bag

This ESP entry level sized spill kit is contained in a clear plastic bag with a zipper. The zipper means that the clear plastic container can be repeatedly refilled and easily resealed. The spill kit is light in weight and easily stores in small spaces. Stash them behind truck seats or in the toolbox. Great for indoor or outdoor use at construction sites or in off-road applications.

This spill kits feature a combination of pads and socks that will contain and recover a 5 Gallon spill of just oil-based fluid as well as the basic equipment needed to handle the clean up process.

Notes

- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all local, state and federal regulations.

Spill kit's contents include:



20 x Pads

size 15" x 18" (38 cm x 46 cm)

The pads in this spill kit are Oil only meltblown sonic bonded polypropylene and will absorb just oil-based fluids.



3 x Socks

size 3" x 4' (8 cm x 1.2 m)

Oil only socks are made with a strong spun-bond outer sleeve and a recycled meltblown polypropylene and cellulose core, producing a resilient no-lint product.



1 x Waste Bag

Waste bags are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

1 pair of gloves

Waterproof gloves help to ensure safe handling of spilled substance.

Compliance

* Basis weights and recycled content are $\pm 5\%$

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(viii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.