Product Datasheet



Cat III Type 5/6 SMS Coverall—BearPro 1





Product Datasheet















International manufacturer to supply, design and produce disposable safety protective products for industry power, food industry, hygiene & cleaning, medical hospital, clean room, beauty salon, household etc

Product Datasheet



Basic Specifications

• Item code: #SC8200(white color)

#SC8208(white color with tape seam)

Brand: BearPro 1

Material: SMS

Colors available: white, blue, red, yellow, green, orange, gray and other colors

Size available: Size S----3XL


Style and design: with hood, elastic wrists and ankles, zipper front with storm flap

Regular Pack: 1pc/poly bag, 50pcs/ctn or other package

Description of Product

BearPro 1 coveralls are made from breathable, durable, comfortable, soft three layers SMS material which is commonly used in many working areas. The SMS coverall is guaranteed to provides the protection against limited splashes and dry particles. The SMS material help reduce the most heat stress which is ideally for the workers in asbestos removal, construction and general maintenance. It's with optimized body fit and increased range of movement.


Stitching Method



Serge seams 4 thread overlocked stitching It's also available to tape seam specially for French market

Fabric Appearance





Product Datasheet



Features

- It's with good breathability and ideal for operatives working in warmer environment.
- Resistance to light limited chemicals, water, dirt, dust.
- Ideally for asbestos removal application
- Many color available like hi-vis color in red, orange and yellow
- Available in tape seam specially for French market

Quality and Protection Level

- Production under ISO:9001:2015
- CE category I PPE Regulation(EU) 2016/425
- TYPE 5 EN ISO 13982-1:2004+A1: 2010 Protective clothing for use against solid particulates
- TYPE 6 EN13034: 2005+A1: 2009 Protective clothing against limited liquid chemicals
- EN ISO 13688:2013: Protective clothing general requirements
- EN 14325:2004 Protective clothing against chemicals







Product Datasheet



Product Design



Product Datasheet




Size Guide



Size						
cm	86-94	94-102	102-110	110-118	118-129	129-141
158-166	SM					
166-174		MD				
174-182			LG			
182-190				XL		
190-198					2XL	
198-206						3XL

Size Measurement



Body measurement in cms in compliance with EN ISO 13688: 2013							
Size	Chest girth	Body Height	Size	Chest girth	Body Height		
SM	86-94	158-166	XL	110-118	182-190		
MD	94-102	166-174	XXL	118-129	190-198		
LG	102-110	174-182	XXXL	129-141	198-206		

Product Datasheet



Test Data

Performance Profile of BearPro 1 SC820X on Fabric								
Physical data	Test method	Result		Class	Class			
Abrasion resistance	EN 530 method 2	>500cycles	>500cycles		3/6			
Puncture resistance	EN 863-EN13034	9.35N		1/6				
Flex cracking Resistance	EN ISO 7854 method B	>100,000 cycles		6/6				
Tensile Strength	EN ISO 13934-1:2013	140N warp,		3/6	3/6			
		57N weft		3/0				
Trapezoidal Tear Resistance	EN ISO 9073-4	24N weft	24N weft		3/6			
		54.2N warp		0,0				
PH value	EN ISO 3071:2006: EN ISO 13688	3.5 > pH > 9.5		Pass				
Amines	EN ISO13688-ISO3071	Pass						
Penetration and repellency on fabric by liquid in accordance with UNI EN ISO 6530:2005+ UNI EN 14325:2005								
		Repellency	Class	Penetration	Class			
H ₂ SO ₄ (Sulphuric acid) 30%	EN ISO 6530-EN13034	>95%	Class 3	<1%	Class 3			
NaOH(Sodium hydroxide) 10%	EN ISO 6530-EN13034	>95%	Class 3	<1%	Class 3			
o-xylene	EN ISO 6530-EN13034		NC		NC			
Butan 1 ol	EN ISO 6530-EN13034		NC		NC			
Performance Profile of BearPro 1 S	C820X on whole suits							
Tensile strength on seams	EN ISO 13935-2	120N	120N		4/6			
Resistance to aerosol penetration Inward leakage type 5	EN ISO 13982-2 – EN ISO 13982	Ljmn 82/90 ≤ 30% L s 8/10 ≤ 15%		Pass				
Resistance to liquid penetration Spray test type 6	EN ISO 17491-4 met. A – EN 13034			Pass	Pass			

Suggested Application

- Hygiene rules
- Industrial manufacturing and maintenance
- Asbestos removal,
- stripping, clear-up or handling
- Construction
- Hospital and Medical

Storage

Please stock the goods in dry environment and avoid direct sunlight. Please don't stock the goods in hot environment to temperature above 25° C and humid above 80%. To keep away from high frequency equipment.

Generally the shelf life is 5 years. We suggest you use products within 3 years.



Product Datasheet




Instruction for use

Please read the instruction sheet before use.. To check the coverall and make sure there is no hole and defect. Open the zipper and put the legs into the coverall, then close the zipper. Choose right coverall size to bring comfortable movement. Please don't re-use if the coverall is broken.

International care symbols:







Do not clean

How to select the appropriate products

Firstly please make sure your purpose for use, then choose the right specification product which can bring you the most comforts and safety. If any doubt, please consult the supplier to get relevant information.

Bestar Industry Technical Dept



A Passion for High-Quality Safety Products Since 2005.