

BULLHEAD SAFETY® EYE PROTECTION



LENS Clear Performance Fog Technology

FRAME Shiny Black

DESCRIPTION

The Chromis™ is a lightweight half-frame design with a 10-base curve wrap-around lens that features dual-injected TPR inner temples for non-slip grip and TPR brow lined to provide flexibility while maintaining durability. This model also features a PFT lens. Thanks to its chemical and physical properties, Performance Fog Technology is an anti-fog lens coating that is permanently bonded to the lens to prevent the formation of condensation on the lenses by absorbing the humidity drops.

Each item is individually packaged in a polybag for retail sale.

FEATURES

- PFT Performance Fog Technology lens: Better than traditional anti-fog! This water-washable, hydrophilic anti-fog lens coating is permanently bonded to the lens to absorb moisture and evenly disperse it, providing clear, fog-free vision
- · Dual-injected inner temples for non-slip grip
- Dual-injected brow lined for frame flexibility without sacrificing durability
- · Temple ends feature a high-visibility alien green color for better visibility
- · Wrap-around lens with 10 base curve
- · Flexible and lightweight half-frame design
- Soft, non-slip TPR nose piece
- Meets ANSI/ISEA Z87.1-2020 standards
- Meets ANSI/ISEA Z87.1-2020 anti-fog properties standard

PACKAGING

	EACH	INNER PACK	CASE
QUANTITY	1	12/box	12 boxes/case
UPC/GTIN	810033299896	10810033299893	20810033299890

13915 Radium St NW Ramsey, MN 55303 763-450-0110 Sales@BullheadSafety.com

TECHNOLOGY

All Bullhead Safety® Eyewear is made from 100% virgin materials. This style features lenses and frames constructed with the highest quality polycarbonate.



MEETS ANSI/ISEA Z87.1-2020 STANDARDS



ANTI-FOG STANDARD



PERMANENT HYDROPHILIC COATING



HARD COAT TREATED LENS



PRESSURE



TAPERED LENS ELIMINATES DISTORTION



LIGHT RAYS

SPECIFICATIONS

LENS	LIGHT TRANSMITTA	NCE FRAME TYPE	FRAME COLOR	WEIGHT
Clear PFT	89%	Half-Frame	Shiny Black	24 Grams
BASE CURVE FRAME WIDTH		TEMPLE LENGTH	END OF TIPS WIDTH	
10	128 mm	120 mm	101 mm	



BullheadSafety.com